

Line Skimmers

Application: Surface Skimming , Containment of Oil and Hydrocarbon in Flowing Water



- Removes sheen
- Does not absorb water
- Oils will not leach or leak
- Silent sentinel -remains on site indefinitely as insurance against potential releases
- Absorbs several times its weight in oil and oil derivatives
- Longer life - will not deteriorate in water
- Transforms pollutant into a stable solid waste
- Waste to energy (BTU value of 10,000)
- Improved safety - no dewatering of oily water after removal
- Reduced risk - No water absorbed means less weight to lift from the water

Description

Line Skimmers are designed to absorb and encapsulate hydrocarbons and oil in non-confined water flows. Line Skimmers are ideal for creating lines of hydrocarbon protection in areas such as ponds and streams as well as clarifying wells and ships in port. The Line Skimmers employ the Smart Sponge® technology which allows water to pass through the product absorbing even sheen levels of hydrocarbons without inhibiting water flow. Line Skimmers are produced in singular, triple, or quadruple and lengths (1.2m and 3.0m).

Applications

- | | | |
|---|--|--|
| <input type="checkbox"/> Stormwater outfall | <input type="checkbox"/> Clarifying Wells | <input type="checkbox"/> Ships Loading/Off Loading at Port |
| <input type="checkbox"/> Ponds and Streams | <input type="checkbox"/> Marine Fuelling Locations | |

Specifications

Single Line Skimmer - single propellant in a plastic net with rings at each end.

Triple Line Skimmer - a bundle of three propellants enclosed in a black plastic net with ropes and clips.

Quad Line Skimmer - a bundle of four propellants with durable sunscreen outer sleeve and metal grommets.

Product	Description	Dimensions	Dry Weight	Packaging
LS104-10	Single Propellant	1.2m long	10kg	10/box
LS110-10	Single Propellant	3.0m long	25kg	10/box
LS304-08	Triple Propellant	2.4m long	17.5kg	8/box
LS310-03	Triple Propellant	3.0m long	21kg	10/box
LS404-05	Quad Propellant	1.2m long	14.5kg	5/box

Handling and Safety

Before using this product, read the label information and the Material Safety Data Sheet. AbTech Line Skimmers are not designed for use in fluid operating temperatures exceeding 55o C. Improper use of Smart Sponge® products may cause them to become structurally compromised, possibly resulting in the loss of absorbent media or obstruction of flow. Long exposure to UV light may result in slight discoloration; this discoloration will not significantly affect performance.